

XETEC design group GmbH
Lengericher Landstraße 30
D - 49078 Osnabrück
phone: +49 / 541 / 7 50 45 - 0
fax: +49 / 541 / 7 50 45 - 45
email: info@xetec.de
www.xetec.de



PRESTIGE SERIES

P-6

COMPONENT SYSTEM

High-End 6" 2-way compo system. The woofer, P-6, is based on the famous Scan-Speak "Revelator" woofer with the unique sliced and coated woodfibre cone and special 6,5" adapter ring, plus the XETEC T-28 Scan-Speak-based tweeter. Both are optimised for car installation and exclusively custom hand-made in Denmark for XETEC. X-overs reside in black aluminium housings. Limited edition!



GRAVITY MODULAR SPEAKER SYSTEM

T-20

TWEETER

Frequency range 3,8 - 20 kHz
Res. Freq. 2,2 kHz
Power Handling (max.) 50 Watt
Impedance 4 Ohm
Outer diameter 41 mm.




TWEETERS

WOOFERS

X-2

CROSSOVER

The X-2 is different from all other speaker X-overs due to the various options of adjustments and adaption of a variety of tweeters and woofers. That offers new possibilities to form your personal speaker system as well as individual sound performance.



T-26

TWEETER

Frequency range 2,8 - 26 kHz
Res. Freq. 1,3 kHz
Power Handling (max.) 60 Watt
Impedance 4 Ohm
Outer diameter 44 mm.



TWEETERS

WOOFERS

T-28

TWEETER

Frequency range 1 - 28 kHz
Res. Freq. 0,6 kHz
Power Handling (max.) 120 Watt
Impedance 4 Ohm
Outer diameter 54 mm.



TWEETERS

WOOFERS



HIGH QUALITY: MKT and aircoils, metal film resistors, aluminium heatsink
CONFIGURABLE: jumpers to adapt to the mounting situation and to the connected speaker systems
FUTURE PROOF: fits all tweeters and woofers of the GRAVITY series. Can be used for future speaker systems as well.

GRAVITY SUBWOOFERS

G-4

WOOFER

Impedance 4 Ohm
Power Handling 80 Watt
Peak Power 100 Watt
SPL 86 dB
Lowest frequency 100 Hz
Diameter 100 mm
Depth 52 mm.



G-10 XLS

SUBWOOFER

Model 4 Ohm
Impedance-minimum 3,2 Ohm
Power Handling 350 Watt
Peak Power 550 Watt
SPL 91 dB
Res. Freq. 39 Hz.



G-5

WOOFER

Impedance 4 Ohm
Power Handling 100 Watt
Peak Power 120 Watt
SPL 88 dB
Lowest frequency 65 Hz
Diameter 130 mm
Depth 55 mm.



G-12 XLS

SUBWOOFER

Model 4 Ohm
Impedance-minimum 3,2 Ohm
Power Handling 500 Watt
Peak Power 750 Watt
SPL 93 dB
Res. Freq. 28 Hz.



G-6

WOOFER

Impedance 4 Ohm
Power Handling 120 Watt
Peak Power 150 Watt
SPL 90 dB
Lowest frequency 45 Hz
Diameter 165 mm
Depth 71 mm.



GRAVITY SUBWOOFERS

G-10XLSG

SUBWOOFER

10" Subwoofer with 27 lt vented Trunk Box, 350 Wrms @ 4 Ohm.



G-12XLSG

SUBWOOFER

12" Subwoofer with 35 lt vented Trunk Box, 500 Wrms @ 4 Ohm.



X-CIRCUIT SERIES

X-4.2

COMPONENT SYSTEM

4,25" 2-way compo with XETEC glassfibre woofer and the new T-20 20 mm soft dome tweeter. Complete stereo set, with all accessories like X-1 crossover, grilles and screws.



X-5.2

COMPONENT SYSTEM

5,25" 2-way compo with XETEC glassfibre woofer and the new T-20 20 mm soft dome tweeter. Complete stereo set, with all accessories like X-1 crossover, grilles and screws.



X-6.2

COMPONENT SYSTEM

6,5" 2-way compo with XETEC glassfibre woofer and the new T-20 20 mm soft dome tweeter. Complete stereo set, with all accessories like X-1 crossover, grilles and screws.



X-CIRCUIT

X-10

SUBWOOFER


4 Ohm, for 27 lt closed enclosure
Power Handling 150 Watt SPL 90 dB
Res. Freq. 38 Hz.



X-10G

SUBWOOFER

10" Subwoofer with 27 lt closed Trunk Box, 150 Wrms @ 4 Ohm.



X-12G

SUBWOOFER

12" Subwoofer with 35 lt closed Trunk Box, 200 Wrms @ 4 Ohm.



XETEC

